



REV.	DESCRIPTION	DATE
A		
B		01-2007



Video Cable Specifications:

- 1 Conductor: OFC Copper (0.12mm*20)
- 2 Core Dielectric: Gas Injected Foam PE
- 3 Shield Braid: OFC Copper (0.12mm/16*4)
- 4 Black PVC Jacket
- 5 Mylar Aluminum Foil



PART NO.	CABLE LENGTH
10R4-03103	3 ft
10R4-03106	6 ft
10R4-03112	12 ft
10R4-03125	25 ft
10R4-03135	35 ft
10R4-03150	50 ft
10R4-03175	75 ft
10R4-031HD	100 ft



3	RCA Male, 24k Gold Plated Connector
2	75 Ohm, Metal RCA Shell
1	CL2 Inwall Rated Component Video, 0.12mm*20 w/Al-Foil + Braid, OD: 6.8mm, Black PVC Jacket
NO.	SPECIFICATIONS

BOM LIST

ITEM NUMBER	10R4-031xx		DRAWER	MPD
TITLE	24K Gold Premium Grade Component Video Cable		CHECKED	MAC
			APPROVED	MAC
MATERIAL		SCALE		
REV.	A	UNIT		
DRAWING NO:			 888-212-8295.com	

REV.	DESCRIPTION	DATE
A		
B		01-2007

ITEMS	CONDITIONS	SPECIFICATIONS
Appearance		No defects such as cracks, scratches or blemishes.
Insertion force withdrawal force	Measurement shall be made after inserting into it's mating plug or socket three times. RCA Plug.	5.88N(0.6Kgf) - 49.0N(5.0Kgf)
Tensile Strength	Between Cable & Connector 49.0N(5.0KGF), 1 Minute	No damage such as displacement or insulation damage, etc
Flexing Test	500G, +/-60 degrees, 1000 Turns 15-20 / Per Min Turns	No damage such as displacement or insulation damage, etc
Insulation Resistance	DC 250V 1 minute between conductors	100 M Ohm or more
Dielectric Strength	AC 250V Shall be applied for 1 minute with trip current 2mA between conductors	Without damage such as electric breakdown
ABS Non-migration	Temperature: 54 +/-1 C Time: 24 +/-1 H Weight: 500 +/-25 G	When visually inspected, any staining of the ABS area that was in contact with the test pieces shall hardly be recognized

ITEM NUMBER	10R4-031xx		DRAWER	MPD
TITLE	24K Gold Premium Grade Component Video Cable		CHECKED	MAC
			APPROVED	MAC
MATERIAL		SCALE		
REV.	A	UNIT		
DRAWING NO:			